

Fujitsu recommends Windows® 7.

Data Sheet

Fujitsu ESPRIMO P400

Desktop PC

Your Immediately Available Office PC

Fujitsu All-round ESPRIMO PCs deliver high-quality computing for your office applications and projects at a very attractive price point. You can choose cost-optimized fixed configurations for immediate delivery. Alternatively, you can use configuration options to meet your specific hardware needs, while staying within your budget.

Intelligent performance

The ideal PC for the day-to-day challenges of office life

- 3rd generation Intel® Core™ i3, Core™ i5, and Core™ i7 processors

Designed and engineered in Germany

Outstanding quality and stable functions based on German production standards

- The development, production and function tests are all under one roof in Germany

Immediate availability

Short waiting-times for fast purchase decisions - pre-configured and always available

- Fast availability and adapted to constantly changing customer and market requirements



Components

Processor	Intel® Core™ i7-3770 processor (4 Cores / 8 Threads, 3.40 GHz, up to 3.9 GHz, 8 MB, Intel® HD Graphics 4000) *
	Intel® Core™ i7-2600 processor (4 Cores / 8 Threads, 3.40 GHz, 8 MB, Intel® HD Graphics 2000)
	Intel® Core™ i5-3470 processor (4 Cores / 4 Threads, 3.20 GHz, up to 3.6 GHz, 6 MB, Intel® HD Graphics 2500) *
	Intel® Core™ i5-2500 processor (4 Cores / 4 Threads, 3.30 GHz, 6 MB, Intel® HD Graphics 2000)
	Intel® Core™ i5-2400 processor (4 Cores / 4 Threads, 3.10 GHz, 6 MB, Intel® HD Graphics 2000)
	Intel® Core™ i5-2320 processor (4 Cores / 4 Threads, 3.00 GHz, 6 MB, Intel® HD Graphics 2000)
	Intel® Core™ i5-2310 processor (4 Cores / 4 Threads, 2.90 GHz, 6 MB, Intel® HD Graphics 2000)
	Intel® Core™ i3-3220 processor (2 Cores / 4 Threads, 3.30 GHz, 3 MB, Intel® HD Graphics 2000)
	Intel® Core™ i3-2120 processor (2 Cores / 4 Threads, 3.30 GHz, 3 MB, Intel® HD Graphics 2000)
	Intel® Pentium® processor G860 (2 Cores / 2 Threads, 3.00 GHz, 3 MB, Intel® HD Graphics)
	Intel® Pentium® processor G850 (2 Cores / 2 Threads, 2.90 GHz, 3 MB, Intel® HD Graphics)
	Intel® Pentium® processor G640 (2 Cores / 2 Threads, 2.80 GHz, 3 MB, Intel® HD Graphics)
	Intel® Pentium® processor G630 (2 Cores / 2 Threads, 2.70 GHz, 3 MB, Intel® HD Graphics)
	Intel® Celeron® processor G550 (2 Cores / 2 Threads, 2.60 GHz, 2 MB, Intel® HD Graphics)
	Intel® Celeron® processor G540 (2 Cores / 2 Threads, 2.50 GHz, 2 MB, Intel® HD Graphics)
	Intel® Celeron® processor G530 (2 Cores / 2 Threads, 2.40 GHz, 2 MB, Intel® HD Graphics)
*with Intel® Turbo Boost Technology (clock speed and performance will vary depending on workload and other variables)	
Operating systems	
Operating system	Windows® 7 Home Basic (EM) 32-bit
	Windows® 7 Home Premium 64-bit
	Windows® 7 Professional 32-bit
	Windows® 7 Professional 64-bit
Operating system compatible	openSUSE Linux
	Windows Vista® (3rd gen Intel® Core™ processors are not supported)
	Windows® XP
Operating system notes	Limited Windows® XP support. Microsoft discontinued Windows® XP certification on system level, basic drivers via http://support.ts.fujitsu.com
Memory modules	
	2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1333 MHz, PC3-10600, DIMM
	4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1333 MHz, PC3-10600, DIMM
Hard disk drives (internal)	
	SSD SATA III, 256 GB, 2.5-inch
	SSD SATA III, 128 GB, 2.5-inch
	SSD SATA II, 128 GB, 2.5-inch, FDE
	HDD SATA III, 7200 rpm, 2000 GB, 3.5-inch
	HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch
	HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
	HDD SATA III, 7200 rpm, 250 GB, 3.5-inch
	HDD SATA II, 7200 rpm, 320 GB, 2.5-inch
	Up to 18 GB of HDD space is reserved for system recovery
Hard disk notes	
Graphics add on cards (optional)	NVIDIA® GeForce® 605 DisplayPort 1GB FH, 1 GB
	DP to DVI-D (single link) Adapter Cable
	ATI Radeon® HD7350 1GB FH, 1 GB
	ATI Radeon® HD 5450, 512 MB

Drives (optional)	BD Triple Writer SATA slim (tray)
	Blu-ray Disc™ Triple Writer
	DVD-ROM
	DVD Super Multi
	MCR 24in1 & USB 3.0 front con., 3.5"
	MultiCard Reader 20in1, USB 2.0, 3.5-Inch
	MultiCard Reader 20in1 USB 3.0 front con., 3.5-Inch
Interface add on cards/components (optional)	MultiCard Reader 24in1 USB 2.0 3.5"
	WLAN III, 802.11g/Draft-n (Windows only)
	USB 3.0 PCIe x1
	Gigabit Ethernet PCIe x1, DS
	Dual serial card PCIe x1, powered
	Dual serial card PCIe x1
Base unit	ESPRIMO P400
Mainboard	
Mainboard type	D2990
Formfactor	µATX
Chipset	Intel® H61
Processor socket	LGA 1155
Processor quantity maximum	1
Memory slots	2 DIMM (DDR3)
Supported capacity RAM (max.)	8 GB
Memory frequency	1333 MHz
Memory notes	Dual channel support. For dual channel performance, identical memory modules in each channel are necessary (minimum 2 modules).
LAN	10/100/1000 MBit/s Realtek RTL 8111E
BIOS version	AMI Aptio 4.6
BIOS features	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI)
Audio codec	Realtek ALC663
Audio features	High Definition Audio
I/O controller on board	
Serial ATA total	4
Controller functions	Serial ATA II (3 Gbit) NCQ AHCI
Interfaces	
Audio: line-in	1
Audio: line-in / microphone	1
Audio: line-out	1
Front audio: microphone	1
Front audio: headphone	1
USB 2.0 total	8
USB 3.0 total	optional
USB front	2
USB rear	4
USB internal	2
VGA	1
DVI	1 (DVI-D)

Interfaces

Mouse / Keyboard (PS/2)	2
Ethernet (RJ-45)	1

Input device / components

Optical USB wheel mouse

Drive bays

Drive bays total	5
3.5-inch internal bays	2
3.5-inch external bays	1
5.25-inch external bays	2

Slots

PCI-Express 2.0 x16	1 x (210 mm / 8.27 inch) Full height
PCI-Express x1	2 x (190 mm / 7.48 inch) Full height

Graphics on board

Graphics brand name	Intel® HD Graphics, HD Graphics 2000, HD Graphics 2500, HD Graphics 4000 (depending on CPU)
Shared video memory	up to 1759 MB
TFT resolution (VGA)	1024 x 768 pixel 1280 x 1024 pixel 1360 x 768 pixel 1440 x 900 pixel 1600 x 900 pixel 1600 x 1200 pixel 1680 x 1050 pixel 1920 x 1080 pixel 1920 x 1200 pixel
TFT resolution (DVI)	1360 x 768 pixel 1440 x 900 pixel 1600 x 900 pixel 1680 x 1050 pixel 1920 x 1080 pixel 1920 x 1200 pixel
Graphics features	Dual display support DirectX® 10.1 or DirectX® 11 (depending on CPU) HDCP support Open GL® 3.3 (depending on CPU) Open CL™ 1.1 (depending on CPU)
Graphics notes	Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size and operating system Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz

Electrical values

	0-Watt mode with hard-off switch
Rated voltage range	200 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Operating voltage range	200 V - 240 V
Operating line frequency range	47 Hz - 63 Hz
Max. output of single power supply	300 W
Monitor outlet	No

Power consumption**Heat dissipation**

Heat dissipation notes	See white paper Energy Consumption
------------------------	------------------------------------

Noise for standard configuration (HDD, ODD)

Noise emission	According to ISO9296
----------------	----------------------

Noise for standard configuration (HDD, ODD)

Related Processors for noise	Intel® Core™ i5 2400
Noise Operation mode 1: ODD load (Blue angel requirement)	5.1 B/ 38 dB(A)
Noise Operation mode 2: HDD load (Blue angel requirement)	4.4 B/ 29 dB(A)
Noise Operation mode 3: CPU 90% load (Blue angel requirement)	4.7 B/ 32 dB(A)
Noise Operation mode 4: High load	4.7 B/ 32 dB(A)
Noise Operation mode 5: Office applications 2.0	4.4 B/ 29 dB(A)
Idle mode (Blue Angel requirement)	4.3 B/ 29 dB(A)
Noise notes / description	A weighted sound power level Lw _{ad} (in B) / workplace related A-weighted sound pressure level Lp _{Am} (in dB(A)), Bystander position

Dimensions / Weight / Environmental

Dimensions (W x D x H)	175 x 425 x 353 mm 6.89 x 16.74 x 13.9 inch
Operating position	Vertical
Weight	9 kg
Weight (lbs)	20.22 lbs
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	10 - 35°C (50 - 95°F)

Compliance

Product	ESPRIMO P400
Model	MI4W-2990
Europe	CE
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL)
Compliance link	https://sp.ts.fujitsu.com/sites/certificates/

Additional Software

Additional software (preinstalled)	Nero Essentials S (burning software) Fujitsu Recovery (Hard Disk Based Recovery) Norton Internet Security (incl. Firewall) 60 days version Microsoft® Office Starter: reduced-functionality Word and Excel® only, with advertising. No PowerPoint® or Outlook®. Buy Office 2010 to use the full-featured software.
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) CyberLink PowerDVD BD (playback software for Blu-ray Disc™, only with Blu-ray Disc™ drive / Blu-ray playback is not supported under Windows XP if the system runs on Intel onboard graphics)

Compatibility (references)

	DMI 2.0 PC 2001 WMI 1.5 USB 2.0 SMBIOS
--	--

Manageability

Manageability technology	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) WoL (Wake on LAN)
--------------------------	--

Security

System protection	Kensington Lock support Eye for padlock
-------------------	--

Security	
Audit proof protection	Boot sector virus protection Control of external interfaces
Access protection	User and supervisor BIOS password Optional: Access protection via external SmartCard reader
Packaging information	
Packaging dimension (mm)	500 x 290 x 540 mm
Packaging dimension (inch)	19.69 x 11.42 x 21.26 inch
Max. quantity / pallet	24
Material - Weight (g) Carton	1270 g
Material - Weight (lbs) Carton	2.8 lbs
Material - Weight (g) EPS / PS	160 g
Material - Weight (lbs) EPS / PS	0.35 lbs
Material - Weight (g) PE	60 g
Material - Weight (lbs) PE	0.13 lbs
Packaging notes	printed user documentation is bleached in chlorine free process
Warranty	
Standard Warranty	1 year
Service level	Bring-In / On-Site Service (depending on country)
Maintenance and Support Services - the perfect extension	
Recommended Service	5x9, Response Time: Next Business Day
Spare Parts availability	3 years
Service Weblink	http://www.fujitsu.com/fts/services/support/index.html

Recommended Accessories

Wireless Keyboard Set LX900



The Wireless Keyboard LX900 is a top of the line desktop solution for lifestyle orientated customers, who want only the best for their desk. This superb keyboard set with offers ambitious users more functions, security and better features than a conventional interface device. It even includes 2.4 GHz technology and 128 AES encryption for security.

S26381-K564-L4** (**:
Country specific variation)

Keyboard KBPC PX ECO



Fujitsu's KBPC PX ECO keyboard is the perfect contribution to Green IT. The keyboard is made out of 45% renewable raw material and comes with a PVC free USB cable. In addition, the KBPC PX ECO offers first class comfort and ergonomics. It attracts attention with its impressive modern design and useful extras.

S26381-K341-L1** (**:
country specific variation)

Keyboard KB900



The KB900 is a very flat keyboard with extra low keys and spill-resistant protection. The elegant design and top-quality construction makes the KB900 the ideal input device for any PC or Notebook user. If you accidentally spill some water or coffee onto the keyboard, this special construction helps the liquid to flow away.

S26381-K560-L4** (**:
Country specific variation)

SOUNDSYSTEM DS E2000 Air



The new more powerful SOUNDSYSTEM DS E2000 Air gives you impressive, well-balanced sound throughout the frequency band. It is an unbeatable USB speaker set with a surprisingly small form factor. The robust satellite speakers are decorated with a deluxe piano finish and the base is adorned with warm ambient lighting.

Order Code:
S26391-F7128-L600

WebCam 130 HD2



With the most advanced HD (High Definition / 720p) recording feature and widescreen video format (16:9 and 16:10), WebCam 130 HD2 can capture up to 30 frame rate per second, close up to HD/720p quality video. Even more: 1-Click-Upload makes the video uploading to YouTube in a snap! With smart clip for notebook & LCD display it is easy to install on any device you want.

Order Code: S26391-F7136-L5

HS E2000 Communicator Headset



The Fujitsu HS E2000 Communicator headset allows you to use your personal computer for Voice over IP (VoIP) in stereo audio quality. This premium headset is designed to provide superb audio quality and comfort for the telephony, internet chat, speech recognition, video conferencing and multimedia applications.

Order Code: S26391-F7139-L5

CELVIN® Drive D100



The CELVIN® Drive D100 is a highly reliable external storage device with a standard USB-interface for easy Plug & Play use with a notebook or PC. It is also easy to set up additional home network capacity by connecting it with dedicated routers or NAS devices.

Order Code: S26341-F103-L118

More information

Fujitsu OPTIMIZATION Services

In addition to Fujitsu ESPRIMO P400, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu ESPRIMO P400, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/fts/ESPRIMO

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT. Please find further information at <http://www.fujitsu.com/global/about/environment/>



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/terms

Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

FUJITSU Technology Solutions
Website: www.fujitsu.com/fts
2012-08-30 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms
Copyright © Fujitsu Technology Solutions